



### **REQUESTED AMENDMENTS TO THE CLAIMS**

Please enter the following currently presented amendments to claims 1, 16, 17, and 19 as indicated below. The newly presented claim amendments do not add any new matter, and are otherwise intended to incorporate material from objected to and otherwise allowable claim language per the Examiner's recent feedback, and are not intended to result in any other substantive effect with respect to their scope. In accordance with 37 C.F.R. §1.121, a claim listing including the status and text of all claims as currently presented appears below. The present amendments do not add any new matter to the subject application.

### **LISTING OF CURRENTLY PENDING CLAIMS**

1. (CURRENTLY AMENDED) An electronics assembly, comprising:
  - a condition-responsive device configured to sense information about at least one physical parameter associated with its surrounding environment;
  - an RF source connected to said condition-responsive device for exciting said condition-responsive device at selected resonant frequency levels such that said condition-responsive device generates an output signal in response thereto;
  - an antenna for receiving said output signal from said condition-responsive device and for transmitting a radio frequency (RF) signal indicating said at least one physical parameter; and
  - at least one switching element configured to selectively control the effective transmission of said RF signal,

wherein said at least one switching element is provided in parallel with said condition-responsive device and is configured to selectively control the effective operation of said condition-responsive device, thus corresponding to selectively cloaking said condition-responsive device,

whereby one or more data types may be selectively transmitted from the electronic assembly.

2. (ORIGINAL) An electronics assembly as in claim 1, wherein said condition-responsive device comprises an acoustic wave device including a plurality of acoustic wave resonators.
3. (ORIGINAL) An electronics assembly as in claim 2, wherein said acoustic wave resonators are surface acoustic wave (SAW) resonators.
4. (ORIGINAL) An electronics assembly as in claim 2, wherein said acoustic wave device comprises a one-port or a two-port resonator-based sensor.
5. (ORIGINAL) An electronics assembly as in claim 1, wherein said condition-responsive device comprises a delay line sensor.
6. (PREVIOUSLY AMENDED) An electronics assembly as in claim 2, wherein said plurality of acoustic wave resonators function to sense information corresponding to the temperature and pressure within its surrounding environment.
7. (ORIGINAL) An electronics assembly as in claim 1, further comprising a power source connected to said RF source.
8. (ORIGINAL) An electronics assembly as in claim 1, further comprising a microcontroller connected to and configured for controlling said at least one switching element.
- 9 – 15 (CANCEL)
16. (CURRENTLY AMENDED) An electronics assembly as in claim [15] 1, wherein said at least one switching element comprises a field-effect transistor (FET).
17. (CURRENTLY AMENDED) An electronics assembly as in claim [15] 1, wherein said at least one switching element comprises a radio frequency identification (RFID) transponder.
18. (ORIGINAL) An electronics assembly as in claim 1, wherein said electronics assembly is integrated with and configured for operation in a pneumatic tire structure or wheel assembly.
19. (CURRENTLY AMENDED) An electronics assembly, comprising:

a condition-responsive device capable of sensing various changes in its surrounding environment, said condition-responsive device characterized by first and second electrical connection points thereto;

an RF source configured for respective connection to said first and second connection points of said condition-responsive device for exciting said condition-responsive device in a given frequency band;

a first switching element coupled between said condition-responsive device and said RF source for selectively controlling the connection between said RF source and a selected connection point of said condition-responsive device; ~~and~~

a second switching element coupled with said condition-responsive device for selectively controlling the effective operation of said condition-responsive device; and first and second antenna wires respectively connected to said first and second electrical connection points of said condition-responsive device, wherein said first and second antenna wires function together as a dipole antenna for said electronics assembly.

20. (ORIGINAL) An electronics assembly as in claim 19, wherein said condition-responsive device comprises an acoustic wave device including a plurality of acoustic wave resonators.

21. (ORIGINAL) An electronics assembly as in claim 20, wherein said acoustic wave resonators are surface acoustic wave (SAW) resonators.

22. (ORIGINAL) An electronics assembly as in claim 19, wherein said condition-responsive device comprises a delay-line sensor.

23. (ORIGINAL) An electronics assembly as in claim 19, wherein said plurality of acoustic wave resonators function to sense information corresponding to the temperature and pressure within its surrounding environment.

24. (ORIGINAL) An electronics assembly as in claim 19, further comprising a power source connected to said RF source.

25. (ORIGINAL) An electronics assembly as in claim 19, further comprising a microcontroller connected to and configured for controlling said first and second switching elements.
26. (ORIGINAL) An electronics assembly as in claim 19, wherein the RF output signals transmitted by said antenna include modulated data effected by selective actuation of said first switching element.
27. (ORIGINAL) An electronics assembly as in claim 26, wherein said modulated data includes information corresponding to at least one parameter selected from the group consisting of tread wear, revolution count, vehicle speed, sidewall deflection level, forces in the tire, and tire identification information.
28. (ORIGINAL) An electronics assembly as in claim 19, wherein selected of said switching elements are field-effect transistors (FETs).
29. (ORIGINAL) An electronics assembly as in claim 19, wherein selected of said switching elements comprise a radio frequency identification (RFID) transponder.
30. (ORIGINAL) An electronics assembly as in claim 29, wherein the operating frequency of said RFID transponder is within said given frequency band for exciting said condition-responsive device.
31. (CANCEL)
32. (ORIGINAL) An electronics assembly as in claim 19, wherein said electronics assembly is integrated with and configured for operation in a pneumatic tire structure or vehicle wheel.
- 33 - 39 (CANCEL)